

www.broadstick.com

Broadstick Cat5e UTP Outdoor PE 24AWG LAN Cable

ROHS

Broadstick provides custom Cat5e UTP Outdoor PE 24awg cable that exceeds the ANSI/TIA 568-B.2 CAT6.

The Broadstick 24awg cable provides high quality connection for Data Centers telecom rooms, equipment distribution areas, desk, etc.

This cable allows easy movements, installations and changes in channels up to 100 meters.

The cable is provided with a cable Outdoor PE jacket and it is of 100% Bare Copper. It includes a Mylar Spirally Wrapped for cables protection.



PAROADSTICK

DETAILS

- Bare copper Solid
- Fluke Certification Channel: 100mts
- Insulation: HD-PE 0.92mm±0.03mm.
- Filler: PE Cross.
- NVP 69%
- 24 AWG.

- Impedance: 100 Ohms.
- Frequency 100 MHz.
- 305 Mts/roll.
- Rating Temperature 30 C.
- Voltage Rating: 30V
- Standard TIA/EIA -568B.2

Part Number	Cord Diameter	Туре	Performance	Description
BSB5EUOU	5.4 mm	UTP OUTDOOR	CAT5E 100Mhz	Cat5E 24 AWG UTP Cable CM BLACK

All Broadstick products are tested in fabric.





www.broadstick.com

		ADSTICK		
Material: Size:	Bare copper Solid 24AWG*4P	Conductor Insulation Insulation Color: 1. Blue&White/Blue 2. Orange&White/Orange 3. Green&White/Green 4. Brown&White/Brown		
Material: Avg.Thickness:	HDPE 0. 21MM			
	S 25mm underneath	CROSS-SECTION ELECTRICAL PROPERTIES		
2.27.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.	(5)	Solid conductor resistance : ≤9.38Ω/100M at 20°C		
Material:		Insulation Resistance : Min. 5000mega ohms-km at 20° Dielectric Tes : 1000V DC/lmin:No Breakdown		
Material: Coverage: Drain Wire:		Delay skew		
Material: Coverage:		Impedance		
		Voltage Rating : 30V Tested : Fluke test passed		
Material:	Nvlon	rtuke test passeu		
Material: Avg. Thickness: Min. Thickness: Diameter:	0.50MM 5.1±0.30mm			
Color:	Optional	Description:LAN CABLE CAT 5e UTP 1/0.5BC*4P PVC		
		Drawing Owen 2022. 11. 21 UNIT: MM REV. : A		
		Checked PAPPOVED APPROVED TO BROADSTICK		
	Material: Size: Construction: Material: Avg. Thickness: Min. Thickness: Diameter: Direction: Pitch: Direction: Pitch: Material: Construction: Material: Coverage: Drain Wire: Material: Coverage: Material: Material: Material: Material: Material: Miterial: Avg. Thickness: Min. Thickness:	Material: Bare copper Solid Size: 24AWG*4P Construction: 1/0.5±0.005MM Material: HDPE Avg. Thickness: 0.21MM Min. Thickness: 0.992±0.03MM Diameter: 0.92±0.03MM Direction: S Pitch: 25mm underneath Direction: S Pitch: 120mm underneath Material: Construction: Material: Coverage: Drain Wire: Material: Direction: Direction: Direction: S Pitch: 25mm underneath Direction: S Pitch: 120mm underneath Direction: Direction: S Pitch: 25mm underneath Direction: S Pitch: 120mm underneath Direc		

All Broadstick products are tested in fabric.

