



## **Fiber Optic Splice Closure – MF48H22**

This fiber optic splice closure provides space and protection for the fiber optic cable splicing and joint. It's water & dust proof and suitable for aerial, duct, wall-mounted or buried applications. It has 4 fiber cable in-out round ports and the cable diameter is from 7-16mm. It is widely applied to the splicing and distributing variable optical cables by aerial, duct and burier.

This product is made of high-quality ABS or PC plastic and with the mechanical seal structure filled with the seal material.

The external component and fastening piece are all made of the high-quality stainless steel. It can be opened after sealing and can be reused without changing sealing material, with silicone rubber insulation tape.



Dimensions: 46.5 X 18.5 X 120mm  
Weight 2.7Kg

### **Features**

- 1, High quality PC, ABS, PPR material optional.
- 2, Used in straight-through and branch application for cables of bundle fiber and ribbon fiber.
- 3, Trays can be increased or reduced according to the application.
- 4, Perfect outline, thunder, erosion & aging resistance.
- 5, Strong and reasonable structure with mechanical sealing structure filled with silicone rubber material, it can be opened after sealing and can be reused.
- 6, Solid structure, easy to operation and maintain.
- 7, Well water & dust proof.
- 8, Suitable for aerial, duct, wall-mounted or buried.

### **Application:**

1. Aerial -hanger
2. Wall-mounting
3. Directly buried